Turret Milling Machines

5 models: M3, M4, M4A, M5, M5A



Photo: JXJ M4

AT A GLANCE

- Table sizes from 1,270 × 254 mm to 1,370 × 305 mm
- Spindle taper R8 or NT30 (M3, M4, M4A); NT40 (M5, M5A)
- Motor 3 HP (M3, M4, M4A) or 5 HP (M5, M5A)
- Usually in stock; special requirements such as supply voltage take 15–20 days

MODELS AND SPECIFICATIONS

Model	Table	X / Y / Z travel	Spindle taper	Spindle speeds	Motor	Slideways	Net weight
M5 (top of line)	1,370 × 305 mm	800 / 440 / 480 mm	NT40	70–3,600 r/min, 10 steps	5 HP	X dovetail / Y-Z box	1,600 kg
M5A	1,370 × 280 mm	800 / 430 / 400 mm	NT40	70–3,600 r/min, 10 steps	5 HP	X dovetail / Y-Z box	1,500 kg
M4	1,370 × 254 mm	820 / 430 / 440 mm	R8 or NT30	80–5,440 r/min, 16 steps	3 HP	X dovetail / Y-Z box	1,400 kg
M4A	1,270 × 254 mm	730 / 400 / 400 mm	R8 or NT30	80–5,440 r/min, 16 steps	3 HP	X dovetail / Y-Z box	1,200 kg
M3	1,270 × 254 mm	760 / 400 / 400 mm	R8 or NT30	80–5,440 r/min, 16 steps	3 HP	Full dovetail	1,200 kg

TERMS

- Warranty: 12 months. For overseas customers: remote guidance and replacement parts.

Specifications are for reference and may be changed without notice; please confirm details with us when ordering.
Quotations are ex-works first, and FOB on request. Minimum order: 1 unit.

To request a quotation: sales@jxjmachinery.com · jxjmachinery.com